

CONCORD *battery*



ADVANCED TECHNOLOGY
THAILAND

CONCORD

battery

Dry Charge

	Battery Type		20 HR (Ref.) CAPACITY (Ah)	5 HR CAPACITY (Ah)	CCA (A) -18°C	CA (A) 0°C	RC Min 25°C	DIMENSION (Approx.mm.)			battery weight (±5%)		Charging Current (Amp)	Battery per Pallet
	New Type No.	Old Type No.						Height	Width	Length	Dry (kg)	Wet (kg)		
JIS	48D26R	N50	50	40	320	400	72	225	173	260	9.2	14.9	5	72
	48D26L	N50L	50	40	320	400	72	225	173	260	9.2	14.9	5	72
	65D31R/L	N70	70	56	410	512	110	225	173	306	12.2	18.7	7	72
	95E41R	N100	100	80	560	700	150	234	176	410	16.2	25.75	10	84
	95E41L	N100L	100	80	560	700	150	257	176	410	16.2	25.75	10	84
	115F51	N120	120	96	740	925	220	257	182	512	21.1	33.5	12	70
	115F51L	N120L	120	96	740	925	220	257	182	512	21.1	33.5	12	70
	135AH	N135/L	135	109	840	1050	225	257	215	512	23.5	37.7	13.5	56
	145G51R/L	N150	150	120	920	1150	250	257	215	512	25	39.4	15	56
	190H52	N200	200	160	1100	1375	390	270	278	521	32.42	51.66	20	56
DIN	67005	DIN170	170	136	1040	1300	300	210	217	513	28.64	42.19	17	56

Tall Tubular Battery

S.No.	Model	Capacity (AH)	DIMENSION (Approx.mm.)			battery weight Kg(±3%)	Battery per Pallet
1	DSNT4010	40 AH	410	292	25.5	49.75	40
2	DSNT6010	60 AH	410	292	28	64.89	36
3	DSNT7520	75 AH	504	254	32.5	73.54	30
6	DSNT8010	80 AH	530	294	32	81.11	30
7	DSNT10020	100 AH	504	254	34.5	93.01	24
8	DSNT15020	150 AH	500	416	58	110.31	20
9	DSNT20020	200 AH	500	416	63	139.51	20
10	DSNT22020	220 AH	500	416	66	148.17	20

Short Tubular Battery

S.No.	Model	Capacity (AH)	DIMENSION (Approx.mm.)			battery weight Kg(±3%)	Battery per Pallet
7	DSNT10020	100 AH					24
8	DSNT15020	150 AH					20
9	DSNT20020	200 AH					20

Flat Plate Battery

S.No.	Container Type	C20 (AH)	Application
1	N120 (115F51R/L)	100 AH	home UPS
2	N135/L (135AH)	120 AH	home UPS
3	N150 (145G51R/L)	135 AH	home UPS
4	N170 (670005R/L)	150 AH	home UPS
5	N220 (220H52R/L)	200 AH	home UPS